



## **ECO PRE-PASTED WALLPAPER 2 INFORMATION**

My Wall Space ECO Pre-Pasted Wallpaper is a premium, **PVC-FREE** white smooth satin finish non-woven wallpaper media for indoors which is permanent (not removable), made with outstanding print quality in mind. It has been designed for hassle-free installation, and can be applied DIY, thanks to its specially formulated pre-pasted glue that allows for multiple applications and is highly recommended for high traffic areas.

### **Sustainable Benefits**

Eco-friendlier with NO PVC with FSC Certification

Utilizes a water-based paste, free from hazardous chemicals.

Digitally printed using HP latex inks, which are Eco logo and Green Guard Gold certified

The environmental performance is the recyclability of used HP consumables. All HP 831 printing supplies—including ink cartridges, printheads, and maintenance supplies are recycled through the HP Planet Partners program.

### **Benefits**

Eco pre-pasted WALLPAPER 2 applies like normal pasted wallpaper.

Permanent adhesion after drying

### **My Wall Space Advice for Extra Protection for High Traffic Areas**

We recommend contacting VIPONDS Paint in Victoria for liquid laminating products for custom printed wallpaper using HP Latex Inks.

Please contact us if you need help

### **Helpful Information**

It is highly recommended to wear cotton gloves during any handling of the printed product.

Indoor application to non-porous, smooth, dry and clean surfaces, which are free from any wallpaper and flaking paint residues.

Paste activation is done by immersing the entire WALLPAPER2 panel into the water tray for a maximum duration of 15 to 30 seconds.

The soaking water must be changed after 6 to 7 immersed panels.

Apply the film within the 2 minutes following its removal from the water.

After application, immediately clean any excess paste with a damp sponge.

It is essential to ensure the walls are wiped clean and free from dust and dirt. Apply with a squeegee ensuring plenty of pressure to get sufficient surface contact with the glue and the paint.

There are many variants in paint. For 100% peace of mind on painted surfaces we recommend testing compatibility prior to use.

Allowing the wall paper to acclimatise in the room it will be applied in for a minimum of 48 hours before application gives the best results.

For damaged walls use a water-based primer/sealant prior to installation, we recommend the Zinsser product range available from most paint and hardware stores. [www.rustoleum.com.au](http://www.rustoleum.com.au)